

**1415****MÓDULO DERIVADOR COM LINHA DE PROTECÇÃO INTEGRADA S2**

Part. 1415 is used to branch up to 4 internal units on the riser (with a different address for each output) and also acts as line protection, isolating the branches in the event of power surges or short circuit. This unit can be used with systems with Simplebus 2 video systems, and as it is powered by the 2 wire bus it does not need any additional power supply. Max. 100 users can be connected to each Mixer part. 4888 or part. 4888C whatever the number of Art. 1415 used, and max. 3 internal units can be connected in cascade for each output of Art. 1415.

**1415****MÓDULO DERIVADOR COM LINHA DE PROTECÇÃO INTEGRADA S2**

Conector de entrada	Terminal de conexão
Certificações	EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

PRINCIPAIS CARACTERÍSTICAS

Altura (mm)	35
Largura (mm)	60
Profundidade (mm)	85
Temperatura de funcionamento (°C)	-25 ÷ 50
Humidade de funcionamento (RH max) (%)	25 ÷ 95
Montagem em guias DIN	Sim
Módulos DIN (n°)	4
Tensão de alimentação	Linha Bus

INFO GERAIS

Tipo de revestimento	Plástico
Cor do produto	Branco

COMPATIBILIDADE

Sistema de áudio/video Simplebus 2	Sim
------------------------------------	-----